

Speaker Mount and Hidden Power

for Sonos One & One SL, WIP

Mounts between studs to any desired location.

PN: C7HSA1-W-WIP-XX, White / C7HSA1-B-WIP-XX, Black

An all-in-one solution that provides wall mounting capabilities and hidden power for Sonos One and One SL wireless speakers.

The Adjustable mounting arm can pivot left or right, up or down and rotate to target the sound direction. This allows for a fully customizable installation.

The un-terminated WIP allows for an unobtrusive installation that can be tied directly into an electrical box, with no visible power cord at the base of the wall.

Available in Black or White



For new construction projects, add on our metal **Speedport™ New Construction Bracket**. Simply fasten to a stud and once the drywall has been laid, the bracket allows installers to use a rotozip opening to ensure proper size and placement of the hole.



PN: SB-2

Un-Terminated WIPs



Wire pigtail end of WIP to nearby electrical box

- Wire directly into nearby electrical box
- No visible power cord at the base of the wall
- Most unobtrusive in-wall power option
- Available in lengths of 15', 25' or 40'

Conforms to STD 514D and Certified CSA STD 22.2 No. 42.1-00
Electrical Rating: 125 VAC, 15 AMPS, 60 Hz
Meets UL 817 & CSA#22.2#21
Interconnect meets UL 2256, 2459
Meets NEC 2014 Article 400.7 (A)(11)
Patented with multiple patents pending.
All rights reserved. Sonos is a registered trademark of Sonos, Inc.



Also Available in 15', 25' and 40' lengths

www.midlite.com

115 Wordell St. Fall River, MA 02721

Tel: 508.676.5169 / Toll Free: 800.606.5169 / Fax: 508.861.0105



Speaker Mount and Hidden Power for Sonos One & One SL, WIP

Mounts between studs to any desired location.
PN: C7HSA1-W-WIP-XX, White / C7HSA1-B-WIP-XX, Black

Installed View

An all-in-one solution that provides wall mounting capabilities and hidden power for Sonos One and One SL wireless speakers.

The Adjustable mounting arm can pivot left or right, up or down and rotate to target the sound direction. This allows for a fully customizable installation.

When ordering, simply replace the '-XX' below with either 15, 25 or 40 for desired length in feet.


- C7HSA1-W-WIP-XX, White
- C7HSA1-B-WIP-XX, Black

(XX = WIP Length, Available in 15', 25' and 40')

For new construction projects, add on our metal **Speedport™ New Construction Bracket**. Simply fasten to a stud and once the sheet rock has been laid, the bracket allows installers to use a rotozip opening to ensure proper size and placement of the hole.



PN: SB-2



(Optional)
New Construction Bracket, PN: SB-2
Install on stud prior to sheet rock,
rotozip opening for Speedport™

2-3/8" HOLE
(HOLE SAW)

MULTI-DIRECTION
SPEAKER MOUNT

SPEAKER POWER
INTERCONNECT

7' SINGLE END
JUMPER

WIP End to be terminated
in an electrical box
Available in lengths of
15', 25', or 40'

SONOS ONE / ONE SL

STUD

Conforms to STD 514D and Certified CSA STD 22.2 No. 42.1-00
Electrical Rating: 125 VAC, 15 AMPS, 60 Hz
Meets UL 817 & CSA#22.2#21
Interconnect meets UL 2256, 2459
Meets NEC 2014 Article 400.7 (A)(11)
Patented with multiple patents pending.
All rights reserved. Sonos is a registered trademark of Sonos, Inc.



www.midlite.com

115 Wordell St. Fall River, MA 02721

Tel: 508.676.5169 / Toll Free: 800.606.5169 / Fax: 508.861.0105

